

Panel PC - VL PPC 6015 AUDI 01 - 2913183

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



IPC with touch screen

Figure may show a different display size

Product Description

IPC with 15" touchscreen display includes an Intel® I7 1.33 GHz processor, 160 GB SATA rotating hard drive, 4 GB DDR3 RAM and MS Windows® 7 operating system. Two RJ-45 Ethernet ports, 4 USB ports, and an RS-232 port provide connectivity and a CompactFlash slot ensures flexibility.



Key Commercial Data

Packing unit	1 pc
GTIN	 4 046356 587389
GTIN	4046356587389
Custom tariff number	84714100
Country of origin	Taiwan

Technical data

Note

Utilization restriction	EMC: class A product, see manufacturer's declaration in the download area
-------------------------	---

Dimensions

Installation dimensions: width, height, depth	386.6 mm x 285 mm
---	-------------------

Display

Display type	38.1 cm/15" TFT
Screen resolution	1024 x 768 Pixel(s) (XGA)

Panel PC - VL PPC 6015 AUDI 01 - 2913183

Technical data

Display

Touch technology	Resistive industrial touch screen
Brightness	350 cd/m ² , typical (adjustable)
Backlighting	CCFL
Display backlight MTBF	50000 h
Colors	16.2 million colors

Computer data

Processor	Intel® Core™ i7-660UE 1.33 GHz
Cooling	active
Operating system	MS Windows 7
RAM	2 GB DDR3 SODIMM
Mass storage	2.5", SATA hard drive
Network	2x Ethernet (10/100/1000 Mbps), RJ45
Interfaces	COM 1 (RS-232), 1x DVI-D, 4x USB, 1x CompactFlash®
Monitor output	1x DVI-D 1x VGA
Slots	without slots
Graphics card	On-board graphics chip (AGP)
Realtime clock	Yes (battery-backed)
Service life of battery	5 years (typical)

General

Mounting type	Installation in front plate
Weight	7.9 kg

Ambient conditions

Degree of protection	IP65 (front), IP20 (back)
Ambient temperature (operation)	0 °C ... 45 °C (Configuration options can affect the operating temperature. See user manual for details)
Ambient temperature (storage/transport)	-40 °C ... 70 °C
Permissible humidity (operation)	5 % ... 95 % (non-condensing)
Permissible humidity (storage/transport)	5 % ... 95 % (non-condensing)
Vibration (operation)	DIN EN 60068-2-6
Shock	15g, 11 ms in accordance with IEC 60068-2-27

Standards and Regulations

Shock	15g, 11 ms in accordance with IEC 60068-2-27
Vibration (operation)	DIN EN 60068-2-6

Environmental Product Compliance

Panel PC - VL PPC 6015 AUDI 01 - 2913183

Technical data

Environmental Product Compliance

China RoHS	Environmentally Friendly Use Period = 50 years
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss

eCl@ss 10.0.1	19200103
eCl@ss 4.0	27250315
eCl@ss 4.1	27250315
eCl@ss 5.0	27360102
eCl@ss 5.1	27360102
eCl@ss 6.0	19200102
eCl@ss 7.0	19200102
eCl@ss 9.0	19200103

ETIM

ETIM 3.0	EC001414
ETIM 4.0	EC001414
ETIM 6.0	EC001414

UNSPSC

UNSPSC 6.01	43172015
UNSPSC 7.0901	43201404
UNSPSC 11	43172015
UNSPSC 12.01	43201404
UNSPSC 13.2	43201404

Accessories

Accessories

Mounting material

Removable hard drive tray - VL I7 HDD TRAY - 2701015



Removable hard drive tray for Valueline IPC with Intel® Core™ I7 processor

Panel PC - VL PPC 6015 AUDI 01 - 2913183

Accessories

Storage medium

Memory card - VL 1 GB CF - 2913155



CompactFlash® card, pluggable, 1 GB

Memory card - VL 2 GB CF - 2913156



CompactFlash® card, pluggable, 2 GB

Memory card - VL 4 GB CF - 2913157



CompactFlash® card, pluggable, 4 GB

Memory card - VL 8 GB CF - 2913158



CompactFlash® card, pluggable, 8 GB

Memory - VL I7 320 GB HDD KIT - 2701012



320 GB, 2.5" SATA HDD kit. Includes tray.

Panel PC - VL PPC 6015 AUDI 01 - 2913183

Accessories

Memory - VL I7 80 GB SSD KIT - 2701013



80 GB, 2.5" SATA solid-state drive (MLC) kit for Valueline IPC with Intel® Core™ I7 processor. Includes tray.