

HF12.5HA-1B





- High-resolution design, providing support for up to 1.5 megapixel camera resolution.
- Low-distortion design achieving accurate image input.
- Compact, lightweight and robust design, supporting various systems
- Focus & iris lock tab provided, supporting environments such as



Focal Length (mm)		12.5
Iris Range		F1.4 ~ F16
Operation	Focus	Manual
	Iris	Manual
Angle Of View (H×V)	2/3"	38°47′ × 29°35′
	1/2"	28°43′ × 21°44′
	1/3"	21°44′ × 16°23′
Focusing Range (From Front Of The Lens) (m)		∞ ~ 0.1
Object Dimensions at M.O.D. (HXV) (mm)	2/3"	78 × 58
	1/2"	57 × 42
	1/3"	42 × 32
Back Focal Distance (in air) (mm)		15.09
Exit Pupil Position (From Image Plane) (mm)		−31
Filter Thread (mm)		M25.5 × 0.5
Mount		С
Mass (g)		45


Remarks

- · With Metal Mount
- · With Locking Knob for Iris and Focus



HF16HA-1B

FIXED




F1.4

METAL



- High-resolution design, providing support for up to 1.5 megapixel camera resolution.
- Low-distortion design achieving accurate image input.
- Compact, lightweight and robust design, supporting various systems
- Focus & iris lock tab provided, supporting environments such as vibration.



MANUAL

Focal Length (mm)		16
Iris Range		F1.4 ~ F16
Operation	Focus	Manual
	Iris	Manual
Angle Of View (H×V)	2/3"	30°45′ × 23°18′
	1/2"	22°37′ × 17°04′
	1/3"	17°04′ × 12°50′
Focusing Range (From Front Of The Lens) (m)		∞ ~ 0.1
Object Dimensions at M.O.D.	2/3"	63 × 47
	1/2"	46 × 34
(H×V) (mm)	1/3"	34 × 26
Back Focal Distance (in air) (mm)		15.15
Exit Pupil Position (From Image Plane) (mm)		−31
Filter Thread (mm)		M25.5 × 0.5
Mount		С
Mass (g)		45

Remarks

- · With Metal Mount
- · With Locking Knob for Iris and Focus

FUJINON CCTV LENS

G-5

GERMANY Phone: +49 89 80902-0

info@stemmer-imaging.de

UNITED KINGDOM

Phone: +33 1 45069560 info@stemmer-imaging.fr

SWITZERLAND Phone: +41 55 415 90 90 info@stemmer-imaging.ch

THE NETHERLANDS BELGIUM · LUXEMBOURG Phone: +31 575 798888 info@stemmer-imaging.nl

