



**Yoke Type Track Rollers**  
**angular-contact ball**  
**single row**  
**series**

**LR 6...NPPU**  
**LR 60...NPPU**  
**LR 2...NPPU**  
**LR 2...NPP**  
 (with cylindrical  
 outside surface)  
**LR 2...RRU**



LR 6...NPPU , LR 60...NPPU , LR 2...NPPU



LR 2...RRU

Outside diameter	Dimensions					$r_{s \min}$	Basic Load rating		Speed rating $n_D$ min <sup>-1</sup>	Code bearing HMEC	Mass ≈ g
	d	D	C	B	d <sub>1</sub>		dyn. C <sub>r</sub> kN	stat. C <sub>or</sub>			
13	4	13	4	-	6	0.2	860	350	24000	<b>LR 604 NPPU</b>	10
16	5	16	5	-	7.1	0.2	1190	490	23000	<b>LR 605 NPPU</b>	10
19	6	19	6	-	8.7	0.3	1740	700	22000	<b>LR 606 NPPU</b>	10
22	7	22	6	-	9	0.3	2130	870	20000	<b>LR 607 NPPU</b>	10
24	8	24	7	-	10	0.3	2750	1250	19000	<b>LR 608 NPPU</b>	20
28	10	28	8	-	14.6	0.3	3650	1700	17000	<b>LR 6000 NPPU</b>	20
30	12	30	8	-	16.6	0.3	4300	2100	16000	<b>LR 6001 NPPU</b>	30
32	10	32	9	-	15.4	0.6	4350	2130	13000	<b>LR 200 NPPU</b>	50
	10	32	9	-	15.4	0.6	4350	2130	13000	<b>LR 200 NPP</b>	50
35	12	35	10	-	17.1	0.6	5600	2700	12000	<b>LR 201 NPPU</b>	50
	12	35	10	-	17.1	0.6	5600	2700	12000	<b>LR 201 NPP</b>	50
	12	35	10	15	18.5	0.6	5500	2700	9000	<b>LR 201 RRU</b>	70
40	15	40	11	-	20	0.6	6500	3300	11000	<b>LR 202 NPPU</b>	70
	15	40	11	-	20	0.6	6500	3300	11000	<b>LR 202 NPP</b>	70
	15	40	11	14.4	21.5	0.6	6500	3300	8500	<b>LR 202 RRU</b>	80
47	17	47	12	-	22.5	0.6	8400	4400	9000	<b>LR 203 NPPU</b>	110
	17	47	12	-	22.5	0.6	8400	4400	9000	<b>LR 203 NPP</b>	110
52	20	52	14	-	26.5	1	10500	5600	8000	<b>LR 204 NPPU</b>	150
	20	52	14	-	26.5	1	10500	5600	8000	<b>LR 204 NPP</b>	150
62	25	62	15	-	30.3	1	12500	7100	7000	<b>LR 205 NPPU</b>	230
	25	62	15	-	30.3	1	12500	7100	7000	<b>LR 205 NPP</b>	230
72	30	72	16	-	37.4	1	16600	9600	5500	<b>LR 206 NPPU</b>	330
	30	72	16	-	37.4	1	16600	9600	5500	<b>LR 206 NPP</b>	330
80	35	80	17	-	42.4	1.1	20200	11900	4500	<b>LR 207 NPPU</b>	400
	35	80	17	-	42.4	1.1	20200	11900	4500	<b>LR 207 NPP</b>	400
90	45	90	19	-	53.2	1.1	22500	13700	3600	<b>LR 209 NPPU</b>	500
	45	90	19	-	53.2	1.1	22500	13700	3600	<b>LR 209 NPP</b>	500